

# RAM Technologies

## PFC400PCX 400 WATT MEDICAL GRADE POWER SUPPLY



The PFC400PCX is a 400 Watt power supply for powering ATX based medical products. The PFC400PCX is available with our Smart Fan low noise option for applications where acoustic noise is an issue. The PFC400PCX is also available with our patented Ultra capacitor based UPS.

MADE IN THE USA

### Specifications

#### Input

Input Voltage Range: 100 to 250 VAC +/-10%  
Supply overvoltage: Cat Two <300V  
Input current: 5.75A MAX  
Frequency: 50/60 HZ  
Inrush Current: 35A Cold @ 264 VAC  
Efficiency: 75% to 80% TYP.  
PFC Correction: Active > .95  
Leakage Current: < 250uA @ 264 VAC 60HZ  
Input Fuses: 2X 6.3A 250V Line & Neutral

#### Output

Max output power: 400 Watts continuous  
Hold-up Time: >40ms @ full load  
Overvoltage Protection: +15% of set voltage  
Thermal Protection: Auto Recovery/ cycle pwr. on  
Minimum Loading: None  
Cross regulation: <0.5%  
Line Regulation: <0.05%  
Load Regulation: <1% +/- cable factor  
AC turn on time: < 2 sec

Output Voltage	+12V	+5V	+3.3V	-12	-5V	+5Vsb
Output current max.	33.3A	30A	28A	1.2A	0.5A	2.0A
Ripple mV P-P	100	50	50	100	50	50

1. Max output from +5V & +3.3V= 180 Watts. When loading the +5 & +3.3V, multiply total load by 1.2 and subtract from 400Watts.

2. Output derates from 100VAC to 85VAC 3.5W/Volt

3. Initial voltage tolerance +/-3%

### Environmental

Operational Temperature: 0 to 50°C  
Storage Temperature: -40 to 80°C  
Operational Humidity: 0 to 95%NC  
Storage Humidity: 0 to 95%NC  
Operational Altitude: -500 to 9840 FT  
Storage Altitude: -500 to 40,000 FT  
Pollution Degree Class: Two

### Reliability

MTBF (demonstrated): > 500,000 hours  
Expected Life: >8 years when use as specified

### EMC Compliance

EN61000-4-2 ESD level3  
EN61000-4-3 RF susceptibility 3v/m  
EN61000-4-4 EFT level3  
EN61000-4-5 Surge Level3  
EN61000-3-2 Harmonics  
EN61000-3-3 Flicker  
EN61000-4-11 Voltage Dips, Short Interruptions  
EN55011 Conducted and radiated emissions

### STANDARDS Compliance

Desktop Platform Form Factors: REV 1.1  
IEC60601-1 2<sup>nd</sup> & 3<sup>rd</sup> edition  
RoHS compliant UL file E191947 ISO9001:2008  
Lead free ROHS and REACH compliant  
Patient Protection: Two MOPP  
ECCN# EAR99

RAM Technologies LLC · 29 Soundview Road Suite 12 · Guilford CT 06437 USA.

Phone: (203) 453 3916 · Fax: (203) 453 3913 · Email: info@ramtechno.com

www.ramtechno.com

# PFC400PCX MEDICAL GRADE POWER SUPPLY


**Safety** Approved to the following standards  
 ANSI/AAMI ES 60601-1:2005 ME-Part 1and CSA C22.2  
 No. 60601-1:08( ME-Part 1: General Requirements for  
 Basic Safety and Essential Performance)  
 IEC 60601-1:2005 (ME Part 1: General Requirements for  
 Basic Safety and Essential Performance – Edition 3)

For Continued protection equipment must be grounded at all times in accordance with the requirements of class 1 devices.

RAM TECHNOLOGIES LLC declares that the PC and PCX power supplies are in conformity with the provisions of the low voltage directive.

See website [DOWNLOADS](#) for enclosure CAD files

## Mechanical Specifications



## Symbols Used

Attention, consult accompanying documents


Protective earth ground

Caution

## Power Good Signal

The Power Good Signal asserts itself high 200ms after all outputs have reached their operational values. Power Good Signal will go low when input stored energy can no longer support the outputs.

**Intended Use:** The PFC400PCX is intended to power imbedded ATX style motherboards in mission critical medical applications.



WE OFFER A WIDE VARIETY OF OUTPUT CABLES PLEASE CONTACT FACTORY FOR DETAILS

RAM P/N  
#620012  
Order #  
0012

GND	Black	1	5	White (+12V)
GND	Black	2	6	White (+12V)
GND	Black	3	7	White (+12V)
GND	Black	4	8	White (+12V)

(GND) Black	1	3	Yellow (+12V)
(GND) Black	2	4	Yellow (+12V)


ATX12V Connector

(+3.3V) Orange	1	11	Orange (+3.3V)
(+3.3V) Orange	2	12	Blue (-12V)
(GND) Black	3	13	Black (GND)
(+5V) Red	4	14	Green (PS-ON)
(GND) Black	5	15	Black (GND)
(+5V) Red	6	16	Black (GND)
(GND) Black	7	17	Black (GND)
(PG) Gray	8	18	White (-5V)
(+5VSB) Violet	9	19	Red (+5V)
(+12V) Yellow	10	20	Red (+5V)

20 Pin ATX Connector

RAM P/N  
#620002  
+  
#620031

(+3.3V) Orange	1	13	Orange (+3.3V)
(+3.3V) Orange	2	14	Blue (-12V)
(GND) Black	3	15	Black (GND)
(+5V) Red	4	16	Green (PS-ON)
(GND) Black	5	17	Black (GND)
(+5V) Red	6	18	Black (GND)
(GND) Black	7	19	Black (GND)
(PG) Gray	8	20	White (-5V)
(+5VSB) Violet	9	21	Red (+5V)
(+12V) Yellow	10	22	Red (+5V)
(+12V) Yellow	11	23	Red (+5V)
(+3.3V) Orange	12	24	Black (GND)



Floppy Drive Power Connector

Example:  
PFC400PCX-0016

24 PIN Optional  
PCI-X Connector

RAM Technologies LLC • 29 Soundview Road Suite 12 • Guilford CT 06437 USA.  
 Phone: (203) 453 3916 • Fax: (203) 453 3913 • Email: info@ramtechno.com

www.ramtechno.com